## DC ELECTRIC SCISSOR LIFTS

	Com	pacts			Co	nvention	als		
	3215	3219	3220	3226	4620	4626	4632	6826	6832
	SPEC	IF	I C A	TIO	NS				
Work Height	21'	25'	26'	32'	26'	32'	38'	32'	38'
	(6.4m)	(7.6m)	(7.9m)	(9.8m)	(7.9m)	(9.8m)	(11.6m)	(9.8m)	(11.6m)
Raised Platform Height	15'	19'	20'	26'	20'	26°	32"	26'	32"
	(4.6m)	(5.8m)	(6.1m)	(7.9m)	(6.1m)	(7.9m)	(9.8m)	(7.9m)	(9.8m)
Lowered Platform Height	34.5°	39°	38°	45°	38"	45"	48.5°	50°	55.5°
	(0.88m)	(0.99m)	(0.97m)	(1.14m)	(0.97m)	(1.14m)	(1.23m)	(1,27m)	(1.4m)
O/A Width	32"	32°	32"	32°	46°	46°	46"	68°	68"
	(0.81m)	(0.81m)	(0.81m)	(0.81m)	(1.17m)	(1.17m)	(1.17m)	(1.73m)	(1.73m)
O/A Length	70°	70°	91.5°	91.5°	91"	91"	91"	99.5"	99.5°
	(1.78m)	(1.78m)	(2.32m)	(2.32m)	(2.31m)	(2.31m)	(2.31m)	(2.52m)	(2.52m)
Stowed Height Railings Up	74°	78.5°	77.5"	84.7°	77°	84.5°	88°	93.5"	99°
	(1,88m)	(1.99m)	(1.97m)	(2.15m)	(1.96m)	(2.15m)	(2.24m)	(2.37m)	(2.51m)
Stowed Height Railings Down	60.1° OPT	64.5" OPT	63.5° OPT	70.6°	63.4° OPT	70.5°	74°	78.5°	84"
	(1.53m)	(1.64m)	(1.61m)	(1.79m)	(1.61m)	(1.79m)	(1.88m)	(1.99m)	(2.13m)
Gradeability Ω									
Capacity ∑	600 lbs	550 lbs	900 lbs	500 lbs	1300 lbs	1000 lbs	700 lbs	1200 lbs	850 lbs
	(272 kg)	(249 kg)	(408 kg)	(227 kg)	(590 kg)	(454 kg)	(318 kg)	(544 kg)	(386 kg)
Platform Width (inside dimension)	26"	26°	28°	28°	42°	42"	42"	57°	57"
	(0.66m)	(0.66m)	(0.71m)	(0.71m)	(1.07m)	(1.07m)	(1.07m)	(1.45m)	(1.45m)
Ptatform Length (inside dimension)	64"	64°	84°	84°	84°	84°	84"	84°	84°
	(1.63m)	(1.63m)	(2.13m)						
Travel Speed	2 mph								
	(3.2 km/h)								
Lift Time ‡	23 sec	25 sec	33 sec	56 sec	32 sec	55 sec	58 sec	65 sec	60 sec
Weight ∑	2400 lbs	2580 lbs	3510 lbs	4135 lbs	4100 lbs	4700 lbs	5075 lbs	5380 lbs	5680 lbs
	(1089 kg)	(1170 kg)	(1592 kg)	(1880 kg)	(1860 kg)	(2132 kg)	(2313 kg)	(2440 kg)	(2576 kg)

		7	
	V	ч	
_	4	-1	
$\boldsymbol{z}$		-	
	1	Z	Z

Analog Based





90° Steering









**Pothole Protection** 



STANDARD FEATURES

Capacity



Foam Filled Tires



**Extension Deck** 



Diamond Pattern Checker Plate Deck



## **Power To Perform**

Since its inception in 1986, Skyjack has become a global leader in the manufacturing of aerial work platforms. Industry leading quality and reliability have become synonymous with the Skyjack brand.

In 2002 Skyjack became a wholly owned subsidiary of the Linamar Corporation. Skyjack is a proud member of the Linamar Group of companies and benefits from a strong corporate culture that fosters continuous improvement through innovative use of technology, unsurpassed work ethic and world class quality and production systems.

Skyjack understands the cost of ownership and makes no compromises when it comes to the integrity of their machines. The lowest available life cycle costs along with the strong residual values makes owning Skyjack equipment a profitable investment.

Skyjack also understands the importance of safety on jobsites and is actively involved on several levels. Skyjack had the first active IPAF/AWPT (International Powered Access Federation / Aerial Work Platform Training) certified training centers in North America.

This literature is for illustrative purposes only. Consult the Operating Maintenance and Parts Manuals for proper procedures. Work platforms have been tested to comply with ANSI and CSA standards as interpreted by Skyjack, inc. Specifications are nominal and subject to change without notice.



A member of the Linamar Group of Companies



## **Corporate Headquarters** Skyjack Incorporated

55 Campbell Road Guelph, Ontario N1H 1B9 Canada

Tel: 519-837-0888 Fax: 519-837-8104 North America: 800-265-2738 Overseas: +1-519-837-0888 E-mail: skyjack@skyjack.com www.skyjack.com

## Distributed by:





SCISSOR ELECTRIC C